



Ferrous in Foil Metal Detectors

www.loma.com

Versatile, proven ferrous in foil metal detection systems for the food and packaging industries



- **Versatile** Range of apertures to suite a wide range of product sizes
- **Easy to use** Automatic product learn ensures maximum sensitivity without adjustment
- **Sensitive** VLF high power coil drive eliminates interference and maximises sensitivity
- **Flexible** Multiple product memories for rapid product change over and data storage
- **Reliable** Heavy duty drives and conveyor parts for the harshest of environments

Metal Detection

X-ray Inspection

Checkweighers

Data Capture

Designed to Survive



Ferrous in Foil Metal Detectors

Finish:	304 stainless steel with bead blast finish		
Standard Line Height:	Feet:	750 - 1000mm (30 - 39")	(50mm steps)
	Wheels:	850 - 1100mm (33 - 43")	(50mm steps)
System Lengths:	Variable to suit application		
Belt Widths:	300/400mm	12/16"	
Typical Belt Speed:	Up to 90 m/min	295' min	
Maximum Weights:	Flat PU Belt	30kg (66lb) on the belt	
	Modular Belt	60kg (132lb) on the belt	
Supply Voltages:	220/230V 1ph N+E or 380/415V 3ph N+E		
Air Supply:	5 to 8 bar		
Reject Types:	Stop on detect	<60kg (132lb)	
	Air blast	<1kg (2.2lb)	
	Pusher	<10kg (22lb)	
	Carriage retract band	<5kg (11lb)	
Environmental Protection:	IP 65 (minimum)	(NEMA 4X)	
Belt Type:	Flat (food quality) belt or Modular Belt		
Options:	Remote control box	Beacon stanchion	Keyboard cover
	Reject confirm	Bin full	LomaNet
	Ethernet	Serial link	Remote reports
	PVS Beacon		

Technical Specification

Upgradeable metal detector controls

High power VLF coil drive

PVS to aid HACCP compliance

Various communication options to suit plant integration protocols

High field strength to eliminate external interference and deliver the ultimate in noise free detection

32-bit digital signal processing for enhanced contaminant detection

Standard apertures on rapid delivery.

Aperture heights = 134mm/184mm

Aperture Widths = 370mm/510mm

USA — Loma Systems Inc, 283 East Lies Road, Carol Stream, IL 60188

Canada — Loma Canada, 333 Wyecroft Road, Unit 11, Oakville, Ontario, L6K 2H2

Tel: 1-800-USA-LOMA

Tel: (905) 842 4581

Fax: (630) 588-0900

Fax: (905) 842 3460

Email: sales@loma.com

Email: lomacanada@loma.com