



# CW<sup>3</sup> DragLink - Dynamic Checkweigher Systems

## Designed for Food & Packaging Industries

### Product Highlights

- For dynamic weighing of end-of-line products including beverages, cans and jars up to 6Kg
- Complete system available with specification including BRC, IFS, & Retail compliance
- Approved systems to OIML R51 and MID (EC TAC)
- Automatic Mean Weight Correction to help meet weight legislation
- Brushless motors & proven conveyor components designed for reliable 24/7 operation



#### Simple Operation with Colour Touchscreen

Icon driven full colour touchscreen control interface, including multilevel password access and data logged events to aid traceability



#### Fast, Simple & Accurate Setup

Type in your product details, initiate setup, and pass a pack several times and the CW3 is automatically set-up and ready to use for average or mean weights



#### Save Money, Reduce Product Give Away

Using a highly reliable loadcell technology the CW3 gives you accurate readings whilst minimising unnecessary product give away





Product Menu [11/11]

Number	Name	Nominal Weight	Date Last Used
0	DefaultProduct	100.0g	09:34 01/11/2016
1	Chocolate	200.0g	09:34 01/11/2016
2	Peanuts	50.0g	09:34 01/11/2016
3	Cake bar	50.0g	09:36 01/11/2016
4	Muffin	33.0g	09:38 01/11/2016
5	Bread	300.0g	09:40 01/11/2016
6	Pastry	65.0g	09:45 01/11/2016
7	Tiger Leaf	500.0g	09:51 01/11/2016
8	Dark Choc	28.0g	09:54 01/11/2016
9	Cookies	40.0g	09:57 01/11/2016
10	Crisps	17.0g	10:01 01/11/2016

#### Switch Products in Seconds with a Library of Stored Products

Up to 500 product calibration details are stored in memory ready for fast product recall using multi-product menus

# Technical Specification




All Measurements in MM

Weight Range (g) MID/R51 Approved	50 - 6000
Weight Range (g) Non - Approved	20 - 6000
Typical Accuracy (g)	0.24
Finish	304 stainless steel
Line Height Options	750,800,850,900,950mm +/- 50mm
Maximum Speed	115m/min
Supply Voltages	110 or 230V/1ph / N+E 50 or 60Hz
Air Supply	5 to 8 Bar (10mm Outside Dia) 72-116 PSI
Operating Temperatures	0-40°C
IP Rating	IP65
Belt Width (Infeed/ Outfeed)	200/300mm (Model Dependent)
Belt Type (Infeed/ Outfeed)	PU Anti Static
Weigh Table	Nylatron GS 1/4 Chain x 3
Reporting	Batch, Shift
Data Retrieval	Via USB, Ethernet, Enet, Tracs

## Automatic Reject Options

The CW<sup>3</sup> is supplied as standard with two output signals suitable for triggering third-party reject systems. Alternatively, it can be specified with an automatic reject station (with retail compliance) with the following options:

- Pusher
- Diverter
- Air Blast



An ITW Company

Loma Systems is a registered trademark of Illinois Tool Works Inc. (ITW). Other names, logos, icons and marks identifying our products and services referenced herein are trademarks of ITW and may not be used without the prior written permission of ITW. Other product and company names listed are trademarks or trade names of their respective companies. Copyright © 2016 Illinois Tool Works Inc. All rights reserved. All of the specifications shown in this document are subject to change without notice.

[www.loma.com](http://www.loma.com)

Tel: +44(0)1252 893300 (UK) | +1-800-872-LOMA (North America)

**Metal Detection | Checkweighing | X-Ray Inspection**

In association with



CW3DL\_893201612